

VX2268WM

22" WIDESCREEN 120Hz LCD

WITH SUPER HD RESOLUTION

Extreme 3D. Ultimate experience.

Experience the next dimension in desktop performance with the ViewSonic FuHzion 22" VX2268wm widescreen LCD. Extreme enough for the hardcore gamer, yet with a refined edge for professional designers, the VX2268wm brings you brilliant, graphics with extreme realism. Powerful performance with revolutionary, pure 120Hz frame rate combined with ultra-fast 2ms video response delivers immaculate blur-free motion and realistic 3D rendering, by connecting directly to your computer / graphic card using the high bandwidth DVI-D DualLink interface. Super HD 1680x1050 resolution with a high contrast ratio adds the right edge to your images. And the integrated stereo speakers bring it all to life. Step into a new world of performance with the 3D ready, 120Hz FuHzion VX2268wm LCD.



Movies and Games at blistering speed

> **Pure 120Hz Frame rate delivers blur-free action**

The 120Hz frame rate refreshes images at twice the speed of standard 60Hz LCDs. This eliminates blur and brings life like reality to games and video.

> **Fast 2ms video response delivers superior picture clarity**

Ultra-fast 2ms video response enables digital HD broadcast-quality video

> **SRS Premium Sound**

Extends the speaker frequency range, delivering better response and sound performance.

> **20,000:1 dynamic contrast ratio**

Provides darker black levels and better overall front-of-screen performance.

> **Stylish slim-bezel design with piano-black finish**

The thin bezel lets you see more without taking up valuable desktop real estate. The high neck and floating head design accentuate the visual experience.



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic®
See the difference™ 

VX2268WM

22" WIDESCREEN 120Hz LCD

ViewSonic®
See the difference™ 



LCD	Size	22" wide Color TFT Active Matrix LCD with 16:10 aspect ratio
	Display Area	474mm(H)×296mm(V) / 18.6in(H)×11.6in(V)
	Optimum Resolution	1680×1050
	Brightness	300 cd/m ² (typ.)
	Contrast Ratio	1000:1(typ.)
	Viewing Angle	170°(H), 160°(V) / 170°(H), 170°(V)
	Response Time	2ms(G to G) / 5ms(typ.)
	Pixel Pitch	0.282mm(H)×0.282mm(V)
	Panel Surface	Anti-Glare, Hard coating(3H)
	Light Source	50,000(Min.)
	Color Support	16.7 M(6-bits FRC)
INPUT	Analog	RGB Analog(75 ohms, 0.7 / 1.0 Vp-p)
	Digital	DVI-D DualLink
	Sync	Separate Sync / Composite Sync / SOG
	Frequency	Fh=24-82 kHz ; Fv=50-75 Hz
COMPATIBILITY	PC	VGA up to 1680×1050 non-interlaced
	Mac	1680×1050 non-interlaced
CONNECTOR	Analog	1 × 15 pin mini D-sub
	Digital	DVI-D Dual Link
	Audio	1 × 3.5 mm Audio in
	Power	Built-in power Adapter, 3-Pin plug
AUDIO	Speaker(W)	SRS Premium Sound
POWER	Voltage	AC 100-240V(Universal) ; 50 / 60Hz(Switch)
	Consumption(W)	47(typ.) / 49(Max.)
	Save mode(W)	≤1
ERGONOMICS	Tilt	Down 5°, Up 20°
CONTROLS	Basic	[1], [2], Power, Down[▼], Up[▲]
	OnView / OSD	Auto Image Adjust, Contrast/ Brightness, Input Select(D-sub, DVI), Audio Adjust : Volume, Mute, Color Adjust : sRGB, 9300K, 7500K, 6500K, 5000K, User Color [R, G, B], Information, Manual Image Adjust : Horizontal Size, H/ V Position, Fine Tune, Sharpness, Dynamic contrast, Aspect ratio, Response time), Setup Menu : Language Select, Resolution Notice, OSD Position, OSD Time Out, OSD Background, Memory Recall
OPERATING CONDITIONS	Temperature	32-104(°F) / 0-40(°C)
	Humidity	10-90%(Non condensed)
DIMENSIONS (W x H x D)	Physical(w / stand)	509mm×441mm×203mm(20"×17.3"×7.9")
	Physical(w / o stand)	509mm×359mm×64mm(20"×14.1"×2.5")
WEIGHT	Net	5.8 kg(12.78 lb)
	Gross (packaging)	7.87 kg(17.53 lb)
REGULATIONS		UL, CUL, FCC-B(ICES), CB, CE, ICES-003B, ERGO, ULAR,NOM, GOST-R, HYGIENIC(20 copies), Energy Star, CCC, BSMI, PSB, C-TICK, MIC(KCC), SASO, WEEE, RoHS, SASO, Ukraine, EPEAT Silver
WALL MOUNT		VESA® 100mm×100mm
POWER MANAGEMENT		Energy Star
PACKAGE CONTENTS		LC Display, Power cable VGA Cable, DVI-D Dual-Link cable Audio cable, Quick Start Guide ViewSonic Wizard CD-ROM



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

Rev.1.0

ViewSonic Europe Limited/UK

Tower 42
25 Old Broad Street
London EC2N 1HQ
United Kingdom
Tel: +44 (0)207 382 8250
Fax: +44 (0)207 382 8251

ViewSonic Germany

Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany
Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France

5 rue de Helder
75009 Paris
France
Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation

381 Brea Canyon Road
Walnut
California 91789-0708
USA
Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Benelux	Tel: +31 (0)20 491 9254
ViewSonic Denmark	Tel: +45 70 22 11 71
ViewSonic Finland	Tel: +358 (0)20 7120 860
ViewSonic MEA	Tel: +971 (0) 4 88 11 871
ViewSonic Norway	Tel: +47 (0) 22 88 17 60
ViewSonic Spain	Tel: +34 (0) 91 63 05 339
ViewSonic Sweden	Tel: +46 (0) 8 50 71 30 00

*Requires SRS Audio Sandbox Software to be installed. **Adapter may be required.

Copyright © 2009 ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies. VS VX2268wm 07/09-UK

For more product information, visit us on the web at ViewSonic.com