



E70 E70fSB E96f+SB G90fB

CRT Size	17"	17"	19"	19"
Viewable Screen Area (cm)	40.6	40.6	45.7	45.7
PerfectFlat®	–	●	●	●
Shadow Mask	●	●	●	●
UltraBrite	–	–	●	–
Diagonal Pitch mm	0.27	0.25	0.25	0.25
Hor. Scanning Frequency (kHz)	30-70	30-70	30-86	30-97
Vert. Scanning Frequency (Hz)	50-160	50-160	50-160	50-160
800 x 600	112	108	132	148
1024 x 768	89	87	105	118
1280 x 1024	67	65	80	89
1600 x 1200	–	–	69	77
1920 x 1440	–	–	–	64
2048 x 1536	–	–	–	–
Max. Mac® Resolution ¹	1024 x 768	1024 x 768	1152 x 864	1920 x 1440
Video Bandwidth (MHz)	120	120	210	240
Screen Treatment	Anti-Static/Anti-Glare	Anti-Static/Anti-Glare	Anti-Static/Anti-Reflection	ARAG
Screen Technology	High contrast	SuperClear	UltraBrite	SuperContrast
BNC connectors	–	–	–	–
Business Audio	–	–	–	–
OnView Controls	●	●	●	●
ViewMatch Colour Control	●	●	●	●
Special Features	VS Wizard CD ROM	VS Wizard CD ROM	VS Wizard CD ROM	VS Wizard CD ROM
Net Weight (kg)	14.0	13.9	18.0	18.0
Power Consumption (Watts typ.)	75	68	55	70
Dimensions (WxHxD mm)	410 x 425 x 402	395 x 395 x 419	445 x 424 x 465	445 x 424 x 465
Emission Standards	MPR II	TCO'03	MPR II	TCO'03
Product Colour				

All CRTs meet the power saving standard: Energy 2000, VESA® DPMS™, EPA ENERGY STAR®², and these ergonomic standards: TÜV/GS, TÜV/Ergo, ISO9241-3,-7,-8, Nemko, Semko, Demko, Fimko, CE, CB

Beige Midnightgrey Metallic on Black ¹ Optional Mac adapter may be required. ² For specific models, only. See datasheets for EPA energy confirmation.